

MATERIAL SAFETY DATA SHEET

Revised: 11/05

Product Name: "URACOA T" 2 COMPONENT URETHANE PART A WHITE
Product Class: Paint

Manufacturer's Identification

Name: NOFIRE TECHNOLOGIES, INC.
Address: 21 INDUSTRIAL AVENUE
UPPER SADDLE RIVER, NJ 07458
Telephone: (201) 818-1616

H.M.I.S. Health: Flammability: Reaction: Personal Protection:

Hazardous Ingredients

(Components may be listed below more than once. Duplicate listings indicate that the component was entered into the formula more than one time. % weight calculations of duplicate components must be added together for total % weight of the component in the product.)

Component Name	Cas#	%Wgt	OSHA PEL	ACGIH	OTHER
CELLOSOLVE ACETATE	110-80-5	12.80	20Oppm	50ppm	

Physical Data

Appearance and Color: WHITE LIQUID
Boiling Range: 276F
Weight Per Gallon: 12, 13
Percent Volatile By Volume: 56.74
Evaporation Rate: Slower than Ether
Vapor Density: Heavier than Air
V.O.C.: 3.72 lbs/gal

Fire And Explosive Data

Flashpoint: 165F (74 ° C) Flammable Limits
D.O.T. Category: COMBUSTIBLAMS Lel: 2 Uel: 4

Extinguishing media: Foam, Co2, Dry Chemical

Unusual fire fighting hazards: Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, and open flames. Closed containers may explode when exposed to extreme heat. Do not apply on hot surfaces.

Special Fire Fighting Procedures: Water spray may be ineffective. Water spray may be used to cool closed containers to prevent pressure build up and possible auto ignition or explosion when exposed to extreme heat. Fire fighters should wear self-contained breathing apparatus.

Health Hazard Data

Eye Contact: Short-term liquid or vapor contact may result in slight eye irritation, prolonged and repeated contact may be more irritating.

Skin Contact: prolonged and repeated liquid contact can cause defatting and drying of the skin, which may result in skin irritation and dermatitis.